



Image quality and speed in one affordable package

The EFI™ H652 UV hybrid printer is the perfect choice for high image quality, quick turn wide-format graphics.



Get in the game with UV hybrid printing

- Photographic image quality at production-level speeds for demanding customers
- Four-colour plus white ink for spot colour and under and overprinting
- Breakthrough vacuum belt media transport system to handle a wide range of flexible and rigid media
- Up to eight levels of variable drop greyscale for near photographic image quality

Ideal Applications:

- Banners
- Display and exhibition graphics
- Flags
- Indoor and outdoor signage
- Industrial–Membrane switch
- Packaging
- Posters
- Point-of-Purchase advertising

Typical Substrates:

- Foam-Cor
- PVC
- Styrene
- Corrugated plastics
- Plywood
- MDO
- Paper
- Aluminium
- Aluminium plastic composite
- Cardboard
- Acrylic
- Glass

Features and benefits

- CMYK plus white
- Up to 42.27 m²/hr
- Up to 1200 x 600 dpi
- Up to eight levels of greyscale

Media/Handling

- Handles flexible and rigid substrates up to 165 cm wide and 4.572 cm thick. Image width 162.56 cm
- Vacuum belt drive system
- Maximum media weight – 34 kg
- Maximum roll diameter – 22.86 cm

Resolution

- 300 x 300 dpi eight levels of greyscale
- 600 x 600 dpi four & eight levels of greyscale
- 900 x 900 dpi four & eight levels of greyscale
- 1200 x 600 dpi eight levels of greyscale

Productivity

- Ultra Quality Mode, 16 Pass, 600 dpi, 7.43 m²/hr
- High Quality Mode, 8 Pass, 600 dpi, 12.1 m²/hr
- Quality Mode, 4 Pass, 600 dpi, 23.69 m²/hr
- Draft Mode, 2 Pass, 300 dpi, 42.27 m²/hr
- White Printing, 1/2 CMYK

Print system

- Five piezoelectric greyscale print heads, up to eight levels of greyscale
- Two shuttered Mercury Lamps with high and low power settings
- One-year printer warranty (excluding consumables)

Formats

- All popular desktop files formats, including PostScript[®]3™, EPS, TIFF, PDF and RGB/CMYK

Genuine EFI inks

- Inks are supplied in 1-litre bottles available in cyan, magenta, yellow, black and white
- Ships with 210C flexible ink set for standard printing applications

Environmental considerations

- Temperature: 18° C to 26.7° C
- Humidity: 20% to 80% (non-condensing)
- Weight: 635.029 kg
- Height: 132.08 cm
- Width: 308.61 cm
- Depth: 101.06 cm without tables
- Depth: 238.76 with tables
- Electrical: 205-234VAC, Single Phase, 50/60Hz, 16 Amps average running; 30 Amp peak supply

EFI Fiery XF digital front end

- Optimised for use with the EFI Fiery XF RIP
- Bi-directional communication capability between the Fiery XF RIP and EFI Wide Format printer allows back communication of audit information on every print job
- Advanced, easy-to-use, wizard-guided colour tools for consistent, predictable, high-quality colour
- Powerful production tools like nesting, step and repeat, scaling, cropping, and tiling
- Advanced ICC colour management for reliable colour, quality output and proofing-quality colour
- Scalable, versatile platform grows with your needs as your business grow
- Three-day, on-site EFI Fiery XF Color & Workflow training available

EFI fuels success.

From Fiery to superwide inkjet, from the lowest cost per label to the most automated business processes, EFI has everything your company needs to succeed. Visit www.efi.com or call 0808 101 3484 or +44 (0)1246 298000 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DocBuilder, DocBuilder Pro, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, Fabrivu, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inkintensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, MiniNet, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printcafe, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, Printstream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Rastek logo, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEK, the VUTEK logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.