



Canon imagePRESS Server L30
Fiery FS350 PRO

Deliver stunning colour and time saving workflow

The Canon imagePRESS Server L30 for the Canon imagePRESS C165 delivers outstanding colour, time-saving workflows and variable data printing capability.

Get outstanding colour every time

Fiery® Edge™ - EFI's next generation colour profiling technology inside imagePRESS L30 Server - produces outstanding print quality. Out-of-the-box, Fiery Edge delivers stunning colour with the smoothest colour blends, maximum shadow details, and superb image definition. Choose new settings to produce more saturated, colourful and dynamic looking prints with this latest colour technology.

To accurately produce brand colours, correct images, and soft proof raster images, use the optional Fiery Graphic Arts Package, Premium Edition with the new Spot Pro capabilities.

Boost your production and profits

The powerful Fiery digital platform enables you to increase productivity with the automation benefits from the free, browser-based Fiery JobFlow™ Base workflow software.

Create personalised print products using the Fiery FreeForm™ Create free application or the supported industry-leading variable data printing (VDP) formats PPML and PDF/VT.

Scale up to more advanced imposition and composition with intuitive optional makeready tools like Fiery Impose, Fiery Compose and Fiery JobMaster.



Canon imagePRESS Server L30 specifications

Fiery Driven™ engines

- Canon imagePRESS C165
- Supports engine finishing devices

Hardware and platform

- Intel® Core™ i3-6100 Processor 3.7 GHz
- 8 GB RAM
- 500 GB SATA HDD
- Internal DVD-RW drive
- 3 USB 3.0 ports (on the side of the Fiery QuickTouch™ panel)
- 4 USB 2.0 ports
- Windows® 10 IoT Enterprise 2016 LTSB
- Fiery FS350 Pro software
- Fiery QuickTouch™ software

File format support

- Adobe® PostScript® Levels 1, 2, 3
- Adobe PDF
- PDF/X-1a, 3, and 4
- Encapsulated PostScript (EPS)
- MS Office document formats: DOC, DOCX, XLS, XLSX, PPT, PPTX, PPS, PPSX, and PUB (via Hot Folders)

Fiery colour and imaging technology

- Fiery ColorWise® colour management technology
- Fiery Edge colour profiles
- Fiery Calibrator
- PANTONE® colour enabled
- Image smoothing
- Fiery Spot-On™
- Image Enhance
- Fiery Image Enhance Visual Editor
- Auto trapping

Productivity and workflow

- Fiery Command WorkStation®
- Fiery drivers for Windows and Mac®
- Fiery WebTools™
- Booklet Maker
- Fiery Hot Folders/Virtual Printers
- Fiery JobFlow™ Base
- Fiery VUE
- Direct mobile printing
- Fiery Go (Android® and iOS)
- Unity Display
- uniFLOW compatible

Performance

- SmartRIP
- Spool-RIP-print simultaneously
- Scan-RIP-print simultaneously
- Sequential Print

Variable data printing

- Supported file formats include:
 - Fiery FreeForm v1 enhanced and v2.1, PPML v3.0, PDF/VT 1 and 2, VPS compatible
- Record and set level finishing support
- VDP record range printing
- Optimized PostScript® and PDF
- Define record length
- VDP raster preview
- VDP Resource Manager

Networking/Connectivity

- TCP/IP, AppleTalk, Bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support

JDF/JMF support

- JDF v1.6 Integrated Digital Printing (IDP) ICS certified
- EFI MIS and Web-to-Print integration ready
- Prepress workflow integration (Agfa® Apogee, Kodak® PRINERGY, Heidelberg® Prinect)

Adobe interpreter support

- CPSI version 3020
- Adobe PDF Print Engine® 4.4 ***

Optional Fiery software and hardware

- Fiery Graphic Arts Package, Premium Edition *
- Fiery Color Profiler Suite **
- Fiery JobMaster™ *
- Fiery Impose *
- Fiery Compose
- Fiery JobFlow *
- Removable hard disk drive kit
- Fiery NX One Station

Security

- Secure erase
- Network protection includes:
 - 802.1x support, IP filtering, port blocking (filtering), SSL support (TLS), certificate management, self-signed certification
- Secure printing

EMI/EMC

- FCC and ICES (US and Canada)
- RCM (Australia and New Zealand)
- CE Mark (EU)
- VCCI (Japan)

Safety

- Intertek - IEC 60950-1:2005 (Second Edition) + Am 1:2009 + Am 2:2013
- Intertek - [UL 60950-1:2007 Ed.2 + R:14Oct2014]
- Intertek - [CSA C22.2#60950-1:2007 Ed.2+A1]
- Intertek - EN 60950-1:2006/A1:2009/A1:2010/A12:2011/A2:2013

Power supply and consumption

- Auto-switching: 100–240 VAC
- 50/60 Hz, 6 Amps @100 VAC
- 3 Amps @240 VAC
- Maximum / typical power usage: 150 W / 60 W

Dimensions

- H: 9.75 in (248 mm); W: 8.0 in (203 mm); D: 15.10 in (384 mm)
- Weight: 13.0 lb. (5.9 kg)

* Free 30-day trial available

** Free trial in demo mode

*** Updated with enhancements and service releases on an ongoing basis

EFI fuels success.

We develop breakthrough technologies for the manufacturing of signage, packaging, textiles, ceramic tiles, and personalised documents, with a wide range of printers, inks, digital front ends, and a comprehensive business and production workflow suite that transforms and streamlines the entire production process, increasing your competitiveness and boosting productivity. Visit www.efi.com or call 0808 101 3484 or +44 (0)1246 298000 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DocBuilder, DocBuilder Pro, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPPhoto, ERegister, EPStatus, Estimate, ExpressPay, Fabrivu, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inkintensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, MiniNet, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printcafe, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, Printstream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Rastek logo, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEK, the VUTEK logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.