

Xerox® EX-P 5 Print Server Powered by Fiery®

XEROX® IGEN® 5 PRESS

Unsurpassed Speed and Performance

The powerful Xerox® EX-P 5 Print Server, driving the Xerox® iGen® 5 Press, features HyperRIP, a unique parallel-processing technology that enables blazing-fast RIP speeds. Two HyperRIP modes (for single and multiple jobs) optimise job processing speed to help achieve uninterrupted production and higher profits.

DRIVE NEW REVENUE WITH A FIFTH STATION

Make a bold, high-value impression on any digital print with Clear, White or Fluorescent Yellow Dry Ink options. Or, add Orange, Green or Blue Dry Inks as a fifth colour to expand your press's gamut, allowing you to match more critical brand colours. Built-in features, such as Fiery® ImageViewer and Fiery® Spot Pro, make it easy to manage any fifth station option throughout your workflow.

OUTSTANDING COLOUR ACCURACY

Get the best out-of-the-box colour consistency and accuracy with Fiery colour management tools. Fiery Colour Profiler Suite allows you to G7® calibrate your Fiery Driven™ iGen 5 Press to ensure colour accuracy throughout print runs and across multiple printers. ICC output profiles are created on the pre-calibrated press for better grey balance.

OPTIMISE WORKFLOW EFFICIENCY AND PRODUCTIVITY

Fiery Command WorkStation® centralises job management and makes getting jobs out the door faster and more efficient. Easily drive multiple presses from one interface and manage multiple jobs simultaneously from a Mac® or Windows® client for maximum productivity. Fiery Impose-Compose offers intuitive, visual document preparation and simplifies labour-intensive assembly. Easily use imposition templates with an automated job submission workflow to reduce touchpoints and errors.

AUTOMATE WITH SEAMLESS INTEGRATION

The EX-P 5 Print Server integrates with technologies such as Xerox® FreeFlow® Digital Workflow Collection plus EFI™ MIS/ERP business software and leading prepress workflows. Boost productivity and profitability by using Fiery JDF technology or the Fiery API to automate and integrate your business and print processes.

The integrated Fiery Smart Estimator allows you to estimate your Speciality Dry Ink usage before you print a single page.



Powered by



xerox™

HARDWARE/PLATFORM

- Fiery® FS300 Pro software
- Microsoft® Windows® 10 IoT Enterprise 2019 LTSC
- Intel® Xeon® Dual 12 Core Processor
- 4 TB HDD for data, 500 GB HDD for OS
- 32 GB high-speed memory
- DVD R/W
- EFI™ ES-3000 Spectrophotometer
- Fiery NX Station GL: Fiery workstand, Fiery Ticker, 22 in. monitor, wireless keyboard, and mouse
- Server touchscreen interface for easy device management and status information with Fiery QuickTouch™ software
- Five USB 3.0 ports (two on rear, three on Fiery QuickTouch panel), two USB 2.0 ports
- Supports all Xerox® iGen® 5 speeds (90/120/150)

FIERY COLOUR TECHNOLOGY

- Fifth station options:
 - Extended Gamut Kit (Orange, Green or Blue Dry Inks)
 - Clear Dry Ink
 - White Dry Ink
 - Fluorescent Yellow Dry Ink
- Spot colour management:
 - Fiery Spot Pro
 - Spot colour groups allow job-specific spot colour priorities
- PANTONE® colour enabled
- CMYK rendering intent control
- Auto-detect Composite Overprint
- Fiery Image Enhance Visual Editor
- Fiery Colour Profiler Suite creates, verifies and edits ICC colour profiles:
 - Enables calibration of iGen 5 Press to G7
- Fiery Graphic Arts Package, Premium Edition provides expert tools for preflighting and troubleshooting jobs
- Full integration with the Xerox® iGen 5 Inline Spectrophotometer and Colour Maintenance Tool

WORKFLOW

- Fiery Command WorkStation®
- Fiery Smart Estimator
- Fiery HyperRIP processes jobs using multiple interpreters simultaneously for faster throughput:
 - Single job or multiple jobs mode
 - Rush RIP immediately RIPs a single job without interrupting other currently RIPping jobs
- Advanced Job Management features such as Rush Printing, Schedule Print, Suspend on Mismatch, Job Reorder, Proof Print and Quick Doc Merge
- CPSI version 3020
- Adobe® PDF Print Engine® (APPE) version 4*
- Adobe Mercury RIP Architecture
- Spool-RIP-Print simultaneously
- Fiery Paper Catalogue integration with the iGen 5 Stock Library
- Object-orientated halftones
- Fiery Hot Folders and Virtual Printers
- PostScript® and PDF X-Objects forms caching
- Configurable Sample Print
- Pad printing

DOCUMENT PREPARATION

- Supports optional XLS (Extra-Long Sheet) capability
- Fiery Impose-Compose offers intuitive, visual document imposition, and is ready to simplify labour-intensive assembly
- Creation of imposition templates for automated job submission
- Enhanced support for offline finishing with slip sheet, job cover page and offset by sheets, copies or sets

VARIABLE DATA PRINTING (VDP)

- Fiery FreeForm™ Create
- Supports the following formats:
 - PPML 2.0/2.2/3.0
 - PDF/VT-1 and PDF/VT-2
 - Creo® VPS compatibility
 - VI Compose, Xerox® VIPP® Language
 - Fiery FreeForm™
- VDP record and set level finishing
- Fiery VDP imposition
- Define record length
- VDP multi-up booklet

FILE FORMAT SUPPORT

- Adobe PostScript Level 1, 2, 3
- PDF/X-1a, 3 and 4
- Adobe Acrobat® XI; Native PDF 1.3, 1.4, 1.5, 1.6 and 1.7
- JPEG, TIFF, TIFF/IT, EPS
- PCL®

NETWORK ENVIRONMENTS/ PROTOCOLS

- JMF (JDF job messaging format)
- TCP/IP, IPP
- Apple® Bonjour® support
- SNMP v3
- Port 9100
- SMB Print Sharing (over TCP/IP)
- FTP printing
- 1 GB Ethernet
- IPv6
- Point and Print (PnP)
- LPR/LPD

SECURITY FEATURES

- Secure Erase
- Back-up and Restore
- Fiery System Restore via WebTools
- IP Filtering for IPv4/IPv6
- User authentication via LDAP
- IP Sec Support
- SSL/TLS support
- Integration with Windows Active Directory®
- SMB hardening
- Windows Defender SmartScreen
- Windows Defender Antivirus
- Enterprise certificate pinning
- Windows Data Execution Prevention
- Port filtering
- Printing privilege/user authentication
- Certificate management
- SNMP v3

DIMENSIONS/WEIGHT

- Print server:
 - Height: 20.75 in (527.05 mm)
 - Width: 9.25 in (234.95 mm)
 - Depth: 22.5 in (463.55 mm)
 - Weight: 21.77 kg
- NX Station GL (without server):
 - Height: 65.6 in (1,665 mm)
 - Width: 31.5 in (800 mm)
 - Depth: 34.9 in (866 mm)
 - Weight: 45 kg

POWER

- Print server:
 - Auto-switching: 100–240 VAC
 - 50/60 Hz, 6 amps @100 VAC, 5 amps @240 VAC
 - Maximum power usage: 600 W
 - Typical power usage: 100 W
- NX Station GL:
 - Auto-switching: 100–240 VAC
 - 50/60 Hz, 1.2 amps

REGULATORY AGENCY APPROVALS

- Meets or exceeds the following requirements:
 - Safety: CB Scheme, IEC 60950-1 Am 2:2013, (TUV/CU mark), CAN/CSA (TUV/CU mark), TUV/T mark
 - Emissions/Immunity: FCC, ICES, EN 55032, RCM, EN 55024, EN 61000-3-2, EN 61000-3-3
 - Emissions: Class A
 - WEEE compliance

FIERY HARDWARE AND SOFTWARE OPTIONS

- Removable hard drive security kit
- Additional Impose licences
- Additional Compose licences

INTEGRATION

- Xerox® FreeFlow® Digital Workflow Collection
- Build unique apps and tools for your business with Fiery API
- Native Fiery JDF integrates creative, production and management information solutions, making digital production faster and more efficient:
 - AGFA® APOGEE™ Prepress, Kodak® Prinergy® Workflow and Heidelberg® Prinect®
 - EFI MIS and Web-to-Print solutions

*Updated with enhancements and service releases on an ongoing basis.

For more information on the Xerox® EX-P 5 Print Server Powered by Fiery®, please contact your Xerox representative, call **+1-800-ASK-XEROX**, or visit us online at xerox.co.uk/igen5.