

A row of colorful, patterned shirts hanging on wooden hangers. The shirts are arranged in a diagonal line, showing various colors and patterns including solid colors, small checks, and larger geometric patterns. The background is a plain, light color.

*efi* JAEGLI EXTENSA

Linea Mercerizzo del Filato

Mercerizzo discontinuo  
per matasse

# Mercerizzo del filato



- YARN MERCERIZING MACHINE
- INOX STEEL – FIXED TANK TECHNOLOGY
- ALS AUTOMATIC LOADING SYSTEM (OPTIONAL)

La nuova macchina per il mercerizzo filo EXTENSA di Jaeggli, dotata di un sistema operativo di controllo elettronico completamente nuovo, porta la mercerizzazione del filo verso nuovi concetti di alta flessibilità operativa, facile ripetitività ed assoluta uniformità, raggiungendo così risultati ottimali nella qualità finale del filo grazie anche all'enorme forza di allungamento di 80 tonnellate.

Il nuovo processo tecnologico, mediante un sistema a vasche fisse, permette l'utilizzo di nuova soda mantenendo sempre i parametri costanti, dopo averla recuperata tramite l'unità di recupero e preparazione della soda ECO-BLOCK.

The ready-made soda lye refills the process tanks enabling the rapid and full soaking of the hanks guaranteeing uniform reaction time of the yarn while the high efficiency squeezing rollers helps firstly the deep penetration of the soda into the fibers and then allow a big saving of money squeezing out most of the residual soda from the hanks.

The model Extensa is finished with inox steel cases and automatic covers and it can be equipped with manual or robotized loading system (optional).

## DATI TECNICI

Yarn type:	<b>cotton and all cellulose fibers</b>
Nominal hanks size:	<b>1372 mm (54")</b>
Hanks size:	<b>1372/2184 mm (54"/86")</b>
Max. loading capacity:	<b>12 kg/cycle (54") - 16 kg/cycle (90")</b>
Max. production:	<b>132 kg/h (with ALS)* or 144 kg/h (with ALS)*</b>
Mercerizing cycle time:	<b>320 sec. (std. cycle) double mercerization available*</b>
Hanks weight:	<b>from 250 up to 1250 gr*</b>
Counts range:	<b>up to Ne 200/2 including single yarns and multi-threads</b>
Stretching force:	<b>up to 80 tons</b>
Squeezing rollers action:	<b>during whole cycle (soda saving)</b>
Stretching rollers:	<b>Lgt. 1600 mm x Ø 210 mm.</b>
Soda consumption:	<b>300 gr - NaOH 100% per each kg of - dry yarn at 30°Bé and 20°C*</b>
Hot water:	<b>200 lt/cycle at 80°C - 100 lt (cycle/recovery)*</b>
Cold water:	<b>100 lt/cycle (recovery)*</b>
Compressed air:	<b>6000 Nlt/h at 6 bar/cycle</b>
Static weight:	<b>10 tons Extensa + 2 tons ALS</b>
Installed power:	<b>16 kW Extensa + 4 kW ALS</b>
Absorbed power:	<b>8 kW Extensa + 2 kW ALS</b>

\*According to our standard cycle

# Eco-block

## All-In-One Compact Unit for caustic soda lye preparation

ALL-IN-ONE COMPACT UNIT FOR CAUSTIC SODA LYE PREPARATION AND CONTINUOUS RECYCLING (WATER AND SODA RECOVERY SYSTEM ON DEMAND)

### ECO-BLOCK SYSTEM

Automatic preparation and supply of caustic soda lye to the mercerizing machines. Absolute parameters in the mercerizing process to obtain easy repetitiveness of the quality. Continuous filtration and recycling of the caustic soda lye.

### ECO-CHILLER

The Eco-Block is predisposed for installation of supplementary chilling unit to cool down the soda lye by means of cooled water through the heat-exchanger.



The Eco-Block is a compact device for preparation and recycling of the caustic soda lye for mercerizing machines. The Eco-Block is completely assembled as compact unit, tested and ready made for connection to all utilities. The standard Eco-Block can supply caustic soda lye for two mercerizing machines type Extensa. For more machines it requires increased cooling capacity.

All-in-one system for filtration (or micro filtration), soda lye concentration regulation, wetting agent dosing, temperature control, cooling device by heat exchanger, predisposition for supplementary chiller (Eco-Chiller).

Eco-Block is absolutely necessary to obtain easy repetitiveness of the top quality in the mercerizing process, batch after batch.

#### DATI TECNICI

Caustic soda flow:	<b>7200 lt/h (tank capacity approx. 1300 lt)</b>
Heat exchanger capacity:	<b>36000 kcal/h min (Eco-Chiller min 42 max. 56 kW)</b>
Installed power:	<b>5kW Eco-Block + 12 kW Eco-Chiller</b>
Absorbed power:	<b>3kW Eco-Block + 7 kW Eco-Chiller</b>
Dimensions (l/w/h):	<b>3,4 x 1,6 x 2,7 mt (static weight max. 3 tons)</b>

## EFI fuels success.

Sviluppiamo tecnologie innovative per la produzione di segnaletica, imballaggi, materiali tessili, ceramica e documenti personalizzati con una vasta gamma di stampanti, inchiostri, front end digitali e una suite di flussi di lavoro e produttivi completa che trasforma e semplifica l'intero processo produttivo aumentando la competitività e la produttività.

Visita [www.efi.com/reggiani](http://www.efi.com/reggiani) o chiama +39 035 3844511 per ulteriori informazioni.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DirectSmile, DocBuilder, DocBuilder Pro, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, Fabrivu, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inkintensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, MiniNet, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printcafe, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, PrintStream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Rastek logo, Remoteproof, RIPChips, RIP-White-Print, Screenproof, SendMe, Sincolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEk, the VUTEk logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries.