

efi REGGIANI IRIS

数码印花专用

水性分散升华墨水

使用我们的水性墨水技术
为您的纺织品锦上添花



使用 EFI Reggiani 数码印花机及 IRIS 的水性墨水为您出色完成打印作业

可扩展色域和高色度令您的数码印花的效果惊艳。此外，它们是两用墨水，无论是升华还是直喷均适用。

这些环保型水性墨水专为充分发挥 EFI™ Reggiani 数码印花机的性能而开发。与我们所有的墨水一样，它们专为 Kyocera 打印头技术而设计，可确保出色的耐用性、更长的打印头寿命和更低的维护成本。



一体化解决方案

- 最丰富的全球经验和知识
- 持续的质量控制
- EFI Reggiani 提供全面的技术支持
- EFI Reggiani 为打印头提供 12 个月的保修期

EFI Reggiani 提供全面的技术支持

- **面料**
 - 聚酯和弹性体面料（莱卡）
- **打印头兼容性**
 - Kyocera KJ4B
- **喷墨温度**
 - 32°C
- **推荐的相对湿度**
 - 50%–60%
- **保质期**
 - 如果在建议条件下储存, 可达 12 个月
- **环境条件**
 - 在低于 25°C 的温度下, 避光避热保存

EFI Reggiani IRIS 墨水有以下颜色可供选择

 青色 SE210C	 品红色 SE220M	 黄色 SE230Y	 黑色 SE200K	 荧光品红 SE260PF
 荧光黄 SE270YF	 蓝色 SE250B	 橙色 SE240O	 浅青色 SE280LC	 浅品红色 SE290LM

应用

- 卓越的升华性能以及针对不同应用（如时装、运动服、家纺和配饰）的直喷。

步骤

- 转印：打印的纸张必须在 200-210°C 的温度下，通过压烫机或热压机进行 30 至 60 秒的热转印
- 直喷：在 190-210°C 的温度下（通过热压机或压烫机）进行 30-60 秒的色彩干燥和定影。直喷可使墨水在热定影过程中进行更好地渗透



色牢度属性

*由 ACCREDIA 实验室认证。

测试	颜色类别 密度	耐光性 100% ISO 105-B02	60°C 清洗 ISO 105-C06	碱性汗液 ISO 105-E04
黑色	B-C	3-4	4-5	4-5
青色	C	4	4-5	4-5
品红色	C	6	4-5	4-5
黄色	B	6-7	4-5	4-5
荧光品红	C	5-6	5	4-5
荧光黄	C	3-4	4-5	4-5
蓝色	C	5-6	4-5	5
橙色	C	5-6	4-5	4-5
浅青色	C	5-6	4-5	4-5
浅品红色	C	6-7	4-5	5

请注意，墨水性能根据最终应用中使用的面料类型可能会有所不同。

EFI 助力成功。

我们致力于为标牌、包装、纺织品、瓷砖以及个性化文档研发出突破性技术，凭借种类繁多的打印机、墨水、数字化前端以一套全面的业务流程和生产工作流程套件，既简化整体生产流程又可相互无缝连接，提升您的竞争力以及工作效率。更多信息请访问 www.efi.com 或拨打 +86 21 3357 6200。



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, Digital StoreFront, DocBuilder, DocBuilder Pro, DockNet, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, FabriVU, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Navigator, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, InkIntensity, Inkware, LapNet, Logic, Metrix, MicroPress, MiniNet, Monarch, OneFlow, Pace, Pegasus, Pegasus Vision, PhotoXposure, PressVu, Printcafe, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, PrintStream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series S0, VisualCal, VUTEK, the VUTEK logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries.

All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.