



VUTEk® FabriVU 180/340
Soft Signage Printers

Drive hard profits with soft signs.

Enter the world of profitable soft signage graphics printing with the EFI™ VUTEk® FabriVU series of digital fabric printers. The industrial platform printers offer everything you need to produce high-quality images at true production level speeds — all while keeping your running cost low and profit opportunity high.



At a glance

- 1.8-metre and 3.4-metre wide aqueous-based soft signage printer models
- Dramatic four-colour printing with a wide colour gamut and deep colour saturation for exceptional fabric display graphics
- Ultra high-resolution up to 2,400 dpi and four level greyscale printing with 4pL to 18pL drop sizes
- Ideal for the production of flags, banners, backlit displays, and other high-end display graphics
- Print direct to textile or transfer paper with the ability to changeover from one to the other
- Auto print head cleaning station increases printer uptime
- Capping station to keep your system up and running
- Patented ink recirculation system for improved ink yield
- Wrinkle detect system protects against costly repairs due to head strikes



EFI VUTEk FabriVU 180

Media/Handling

- Prints up to 180 cm wide
- Fabric weight from 45 to 450 gr/m²
- Paper weight from 28 to 140 gr/m²
- Entry and exit: standard roll unwinder/rewinder up to 450 mm outside diameter
- Dryer: heated platen

Resolution

Up to 2,400 dpi

Productivity

- Production speeds (max.) up to 400 m² per hour
- Production image quality: 200 m² per hour
- POP image quality: 132 m² per hour

Formats

All popular desktop file formats, including PostScript[®]3[™], EPS, TIFF, PDF, RGB/CMYK

Environmental considerations

- Temperature: 20-24 °C
- Humidity: 50-60%
- Weight: 3,000 kg

- Printer, platen, and winders dimensions (L x W x H): 230 cm x 454 cm x 180 cm
- Printer electrical: 3 Phase, 400V, 50Hz, 35kW
- Water pressure: min. 1.5 bar; max. 2 bar
- Water volume: 5 litres per hour
- Water temperature: 20-25 °C


EFI Fiery proServer

- Colour management workflow and RIP optimised for VUTEk printers*
- Advanced, yet easy-to-use, colour tools for CMYK profile creation and quality control
- EFI ES-2000 spectrophotometer
- Powerful nesting, step and repeat, scaling, cropping, tiling, and cut marks production tools
- Fiery[®] station, including furniture, keyboard, and mouse
- Two-day on-site Fiery colour and workflow implementation services

* Check the latest Fiery proServer specifications and availability for this printer on efi.com

Genuine EFI Inks

Water based CMYK dispersed dye inks



EFI VUTEk FabriVU 340

Media/Handling

- Prints up to 340 cm wide
- Fabric weight from 45 to 450 gr/m²
- Paper weight from 28 to 140 gr/m²
- Entry and exit: standard roll unwinder/rewinder up to 450 mm outside diameter
- Dryer: heated platen

Resolution

Up to 2,400 dpi

Productivity

- Production speeds (max.) up to 500 m² per hour
- Production image quality: 250 m² per hour
- POP image quality: 165 m² per hour

Formats

All popular desktop file formats, including PostScript[®]3[™], EPS, TIFF, PDF, RGB/CMYK

Environmental considerations

- Temperature: 20-24 °C
- Humidity: 50-60%
- Weight: 4,800 kg

- Printer and dryer dimensions (L x W x H): 230 cm x 615 cm x 180 cm
- Printer electrical: 3 Phase, 400V, 50Hz, 35kW
- Water pressure: min. 1.5 bar; max. 2 bar
- Water volume: 5 litres per hour
- Water temperature: 20-25 °C

EFI Fiery proServer

- Colour management workflow and RIP optimised for VUTEk printers*
- Advanced, yet easy-to-use, colour tools for CMYK profile creation and quality control
- EFI ES-2000 spectrophotometer
- Powerful nesting, step and repeat, scaling, cropping, tiling, and cut marks production tools
- Fiery station, including furniture, keyboard, and mouse
- Two-day on-site Fiery colour and workflow implementation services

* Check the latest Fiery proServer specifications and availability for this printer on efi.com

Genuine EFI Inks

Water based CMYK dispersed dye inks

EFI fuels success.

We develop breakthrough technologies for the manufacturing of signage, packaging, textiles, ceramic tiles, and personalised documents, with a wide range of printers, inks, digital front ends, and a comprehensive business and production workflow suite that transforms and streamlines the entire production process, increasing your competitiveness and boosting productivity.

Visit www.efi.com or call 0808 101 3484 (UK only) or +44 (0)1246 298000 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, Digital StoreFront, DirectSmile, DocBuilder, DocBuilder Pro, DockNet, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, FabriVU, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Navigator, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, InkIntensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, Metrix, MicroPress, MiniNet, Monarch, OneFlow, Pace, Pecas, Pecas Vision, PhotoXposure, PressVu, Printcafe, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, PrintStream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEk, the VUTEk logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries.

All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.